


PRODUCT GUIDE



> Identification



IMAGE BASED BAR CODE READERS

APPLICATIONS

MATRIX 450™

Transportation and Logistics

- Automated sorting
- Manual postal sorting
- Loading / unloading

Distribution & Retail

- Order fulfillment and verification
- Multimedia sorting
- Reverse logistic processes
- Static scanning

STS400™

Transportation and Logistics

- Postal and courier express sorting
- Solution for tires traceability and sorting
- Revenue recovery

Distribution & Retail

- Large distribution centres
- Multimedia sorting
- Receiving / shipping systems

XRF410N™

- E-Commerce
- General material handling with reusable totes
- End-of-line
- Postal Sorting
- Medium object sortation for couriers

AV7000™

Transportation and Logistics

- Postal and courier express sorting
- Revenue recovery
- Reverse logistic processes
- OCR and Videocoding
- Extended ID and Image saving

Distribution & Retail

- Large distribution centres
- Multimedia sorting
- Receiving / shipping systems

HIGHLIGHTS

MATRIX 450

- Very large reading area, FOV and DOF
- Outstanding dynamic reading capabilities, up to 3.2 m/s on 0.30 mm resolution 1D code
- White and Blue illumination options
- Packtrack function for object gap tolerance up to 50 mm (2 in)
- ID-NET™ readers clustering to extend the reading area coverage on single side and multi-side applications
- Persistent Image Saving on specific reading results (No Read) for diagnostics or reporting

STS400

- Easy to install: 100% pre-assemble calibrating
- Easy to maintain
- Simple and lean: simple and regulated render layout which avoids articulated mounting patterns
- Long-term reliability: no moving on board guarantee reliability and longer life-cycle
- Ready for the future: compatible with changing requirements such as downsizing of code heights or introduction of cd codes

XRF410N

- Easy to select the correct model
- Easy to install
- Increase customer productivity
- Ease of use
- Solves the most demanding sortation applications
- Easy to monitor and validate status

AV7000

- Single view high quality picture on large conveyor (1400 mm/55 inch)
- Excellent reading performances on high speed conveyors: 4.8m/s (945fpm)
- Patented Pulsed Lighting System to reduce reading station footprint 2.2m (7ft)
- Patented Autofocus System offering extended DoF
- Patented Digital Zoom technology assuring constant DPI resolution
- New generation decode algorithm to read very bad quality label
- Multiple format Image saving from full definition to highly compressed JPG
- Integration with dimensioning and scale system

TECHNICAL DATA

MATRIX 450

- 5MP image sensor, 15 FPS
- Gigabit Ethernet Integrated Connectivity
- C-Mount Lenses, focal length: 16 mm, 25 mm, 35 mm, 50 mm
- Data output: RS232/RS485, Ethernet
- I/O: 2 inputs, 2 outputs; optocoupled
- Protection class: IP65
- Operating temperature: 0°C to 50°C
- Supply Voltage: 24 Vdc ± 20%

STS400

- 5 to 8 clustered Matrix 410
- 2 MPixels imagers sensor
- Interfacing CBX500 with display and back up memory
- Persistent Image Saving on specific reading results (No Read) for diagnostics or reporting
- IP67, 0-50° operating temperature
- Ethernet, Profinet and Ethernet IP embedded

XRF410N

- Full working solutions in one order number
- Factory calibration, optimized for code resolutions 0.25 mm, 0.33 mm, 0.38 mm
- Factory calibration, optimized for speeds up to 2.2 m/s
- Packtrack 2D embedded, for short objects gap
- Ethernet connectivity on board
- Power supply: 24 VDC
- Protection class: IP67

AV7000

- CCD sensor: 8192 pixels
- Image resolution: 110-260DPI (application dependant)
- Scan rate: 33KHz
- Readable symbologies: all standard 1D and 2D codes
- High quality Image for OCR and Videocoding
- Connectivity: RS232/RS485, Ethernet
- Video output: Gigabit Ethernet, CC-Link
- Protection class: IP65
- Operating temperature: 0°C to 50°C



STS400



AV7000



MATRIX 450



XRF410N

IMAGE BASED BAR CODE READERS

APPLICATIONS

MATRIX 210N™

Electronics

- PCB board tracking
- Electronic product tracking

Medical & pharmaceutical

- Medical device traceability
- Pharmaceutical supply chain traceability

OEM

- Chemical & biomedical analysis
- Access control systems
- Self service systems (ATM, kiosks)
- Print & apply systems
- Document handling

MATRIX 300N™

Manufacturing, Electronics and Automotive

- DPM code validation after marking
- Work-in-progress control
- Parts and assemblies traceability

Food and Beverage

- Work-in-progress traceability

Document Processing

- High speed process control

Medical

- Medical device traceability

Clinical Lab Automation

- Biomedical analysis machines
- Specimen collection machines

Logistics Automation

- Carton and tote traceability
- Automated warehousing

MATRIX 410N™

Automotive

- Part traceability in assembly

Distribution & retail industry

- Manual Presentation
- Small Objects Sorting
- Totes content scanning

Medical & pharmaceutical

- Automated storage/retrieval
- Automated Order fulfilment/validation

Warehouse

- End of line, Carton/objects, single or multi-side scanning

HIGHLIGHTS

MATRIX 210N

- Integrated Ethernet, PROFINET, EtherNet IP
- Electronic focus control option
- High performance DPM bar code reading
- Outstanding decoding capability on DPM and labeled 1D & 2D standard codes
- Straight and right angle models for smart mounting
- ID-NET™ reader clustering/networking
- Industrial Protection: ESD-safe, YAG, IP65

MATRIX 300N

- Ultra-compact dimensions
- High performance DPM reading
- Liquid Lens Dynamic Focus Control
- Integrated dual illuminator: dark field/ bright field
- Fast and high resolution image sensor
- Power over Ethernet Option and onboard PROFINET-IO
- Extreme Industrial grade: IP65-IP67 Industrial grade for harsh environments, 0-50°C operating temperature

MATRIX 410N

- Patented continuous high power mode lighting
- Patent Pending Packtrack 2D for short object gapping in sortation applications
- Embedded Ethernet connectivity, with common protocol support: Profinet, EtherNet IP, TCP/IP, FTP, HTTP
- On board image storage saving up to 3,000 image (scaled)
- External connection box with parameter back up memory and display
- Remote, web-based WebSentinel software with image archiving database

TECHNICAL DATA

MATRIX 210N

- Extremely compact dimensions: 50x25x45mm & 54x45x32mm
- High speed integrated EtherNet for real time image transfer
- WVGA image resolution, 60 frames/s
- Object speed: up to 2.0m/s
- Connectivity: Ethernet 10/100: EtherNet IP, PROFINET, TCP/IP, UDP, FTP, MODBUS TCP Serial RS232/RS422/RS485 up to 115.2 Kbit/s + Aux RS232
- IP65, 0-50°C

MATRIX 300N

- Manual and electronic focus control
- CMOS global shutter sensor
- 1280 x 1024 (1.3 megapixels) image resolution
- Read rate: 60frames/s
- Connectivity: Ethernet 10/100: EtherNet IP, TCP/IP, UDP, FTP, MODBUS TCP, Serial RS232/RS422/RS485 up to 115.2 Kbit/s + Aux RS232,
- On-board PROFINET-IO
- IP65-IP67, 0-50°C

MATRIX 410N

- Operating temperature:
 - Manual Focusing models: 0° to +50 °C (32 to 122°F)
 - Electronic Liquid Lens models: -20° to +70 °C (-4 to 158°F)
- Power supply: 10 to 30VDC; 8W max.; 5W typical
- Protection class: IP65-IP67
- CMOS global shutter sensor
- MATRIX 410N -5xx-xxx:
 - 1.3 MP (1280 x 1024) image resolution, 60 frames/s
- MATRIX 410N -7xx-xxx
 - 2.0 MP (1600 x 1200), 45 frames/s
- Connectivity: Ethernet 10/100: Ethernet IP, PROFINET, TCP/IP, UDP, FTP, MODBUS TCP Serial RS232/RS422/RS485 up to 115.2 Kbit/s + Aux RS232
- IP 67, 0-50°C



MATRIX 210N



MATRIX 300N



MATRIX 410N

LASER BASED BAR CODE SCANNERS

APPLICATIONS

TC1200/DS1100

- Access control systems
- ATL (Automated Tape Libraries)
- Self service systems (ATM, kiosks)
- OEM integration in automatic machines
- Game automation (Lotto, Lottery, etc.)
- Chemical and blood analysis machines
- Print & apply systems
- Film processing machines

DS1500/DS2200

- OEM integration in automatic machines
- Chemical and biomedical analysis machines
- Document handling machines
- Print & apply systems
- High speed pharmaceutical packaging
- Packaging machines
- ATL (Automated Tape Libraries)

DS6300/DS6400

- Automated warehousing
- Electronic industry manufacturing
- Shopfloor on automotive, electric appliances, food & beverage
- Sorting on logistic and distribution lines
- Omni-sorting on small conveyors

HIGHLIGHTS

TC1200

- Cost-effective
- Embedded code reconstruction software
- Very high density code reading (up to 0.1mm / 4mils)
- Scanner and scan engine version
- No moving part (MTBF>200.000 hours)
- Designed for OEM integration

DS1100

- Cost-effective
- Direct or 90° reading window
- Motor on/off SW control
- Designed for OEM integration

DS1500

- Extremely compact size
- Excellent reading capabilities
- Designed for OEM integration
- ACB™ Advanced Code Builder
- Motor on/off SW control

DS2200

- Compact dimensions
- Excellent reading capabilities for high density codes
- Designed for OEM integration
- Very high density code reading (up to 0.076mm / 3mils)

DS6300 / DS6400

- Adjustable or Flash™ (Dynamic) laser optics
- Step-A-Head™ feature
- ACR4™ Advanced Code Reconstruction available
- Integrated oscillating mirror models available
- Built-in connectivity to Ethernet/ Devicenet/ Profibus networks
- PackTrack™ tracking system
- Embedded display and keypad
- Multilanguage Genius™ configuration tool

TECHNICAL DATA

TC1200

- CCD reader
- Scan rate: up to 320scans/s
- Reading range: 50 to 430mm
- Max. resolution: 0.1mm (4 mils)
- RS232 and USB model
- Power supply: 5VDC, 2W max.

DS1100

- Scan rate: up to 500scans/s
- Reading range: 10 to 220mm
- Max. resolution: 0.127mm (5mils)
- Motor on/off via software commands
- Power supply: 5VDC, 2W max.
- Protection Class: IP65

DS1500

- Dimensions: 40x30x22mm
- Scan rate: up to 1200scans/s
- Reading range: 40 to 240mm
- Max. resolution: 0.10mm (4mils)
- Test mode with bar graph
- Power supply: 5VDC, 2W max.
- Protection class: IP65

DS2200

- Dimensions: 50x40x28mm
- Scan rate: 500scans/s (1000scans/s on demand)
- Reading range: 50 to 200mm
- Max. resolution: 0.076mm (3mils)
- Power supply: 5VDC, 2W max.
- Protection class: IP65

DS6300 / DS6400

- Optics: adj. (DS6300) Flash™ (Dynamic) (DS6400)
- Scan rate: Up to 1200scan/s
- Reading range: 300 to 2000mm (DS6300) 300 to 2500mm (DS6400)
- Max. resolution: up to 0.2mm (8mils)
- Connectivity: RS232, RS485, EtherNet IP, Ethernet TCP/IP
- I/O: 4 inputs, 3 outputs; optocoupled
- Power supply: 15 to 30VDC, 15W max.



LASER BASED BAR CODE SCANNERS

APPLICATIONS

DS8110/DX8210

- Airport Baggage Handling
- Parcel Sorting
- Retail Distribution Center
- Loading/Unloading System
- Shop Floor and Manufacturing
- Automatic Warehousing Management

HIGHLIGHTS

DS8110

- Top Class Reading Performance
- Excellent performance on Low quality code
- Ethernet Bus Connections for high speed data transmission and real time synchronization
- Fully redundant configuration, no single point of failure
- Compact mechanical dimensions
- Ease of use and ease of installation
- Modular architecture and building block configurations
- Ease maintenance and automatic replacement

DX8210

- ALL-IN-ONE architecture offering outstanding ease of use and installation
- Excellent performance on Low quality code
- Unmatchable ease of use and ease of installation
- DST (Digital Signal Technology) offering stable and constant performance at any operative conditions
- Ethernet Bus Connections for high speed data transmission and real time synchronization
- Fully redundant configuration, no single point of failure
- e-GENIUS web browser programming tools
- Ease maintenance and automatic replacement

TECHNICAL DATA

DS8110

- Scan pattern type: linear
- Scan rate: 1000 scans/s
- Reading range: 500 to 1900mm
- Max. resolution: min 0.25mm/max 0.50 mm
- Dimensions: 216 x 96 x 127 mm [8.5 x 3.8 x 5 in]
- Protection class: IP65
- Operating temperature: 0°C to 50°C

DX8210

- Scan pattern type: X-Pattern
- Scan rate: 1000scans/s
- Max. resolution: min 0.25mm/max 1.0 mm
- Dimensions: 381 x 328 x 92.5 mm [15 x 13 x 3.6 in]
- Protection class: IP65
- Operating temperature: 0°C to 50°C

AXIOM™

- Postal/Parcel sorting and tracking
- Automated warehousing identification systems
- Airport baggage sorting systems
- Cargo applications
- Receiving / shipping systems

AXIOM

- Scanning over 1,2, or 4 read zones for the largest reading zones
- DRX barcode reconstruction software for reading skewed barcode labels
- Modular scan head and wiring base for simple replacement
- Parameter storage modules makes replacement quick and easy
- Flexible Connectivity

AXIOM

- Scan pattern type: X-Pattern type
- Scan rate: 1000 scans/s
- Reading range: 380mm to 1830mm
- Dimensions: 158mm x 276mm x 132mm
- Protection class: IP65
- Operating Temp: 0°C to 50°C
- Connectivity: RS232/RS422, Ethernet TCP/IP, EtherNet IP, DeviceNet, Profibus

AXIOM™-X

- Postal/Parcel sorting and tracking
- Automated warehousing identification systems
- Airport baggage sorting systems
- Cargo applications
- Receiving / shipping systems

AXIOM-X

- Omni-directional scanning
- Highest Read performance
- Largest Coverage
- Fastest Installation
- Easy 'Plug and Play' replacement

AXIOM-X

- Laser pattern: cross
- Scan rate: 1120 scans/s
- Reading range: out to 2032mm
- Dimensions: 311mm x 354mm x 176mm
- Protection class: IP654
- Operating Temp: 0°C to 50°C
- Connectivity: RS232/RS422, Ethernet TCP/IP, EtherNet IP, DeviceNet, Profibus



DX8210



DS8110



AXIOM-X



AXIOM

LASER BASED BAR CODE SCANNERS

APPLICATIONS

DS2100N / DS2400N

Automated warehousing

- Conveyor sorting
- Picking systems
- Automated storage and retrieval systems
- Tote Reading

Automated Shopfloor

- Item and part tracking
- Process control and packaging
- Packaging and compliance

OEM

- High speed document handling machines
- Print & apply systems
- Automatic chemical and biomedical analysis machines
- Reverse vending machines (can and bottle recycling)

HIGHLIGHTS

DS2100N / DS2400N

- Embedded Ethernet connectivity
- Two Profinet Ports
- Embedded Ethernet Switch
- Line topology
- Rotating connector block
- Compact dimensions
- Installation flexibility and optimum form factor
- ACR: Advanced Code Reconstruction
- Excellent performance on low quality and damaged labels
- DS2100: Up to a 300 mm (11.8 in.) reading distance
- DS2400: Up to a 600 mm (23.6 in.) reading distance

TECHNICAL DATA

DS2100N

- Scan rate: up to 1000scans/s
- Reading range: 50 to 300mm
- Max. resolution: 0.12mm (5mils)
- Power supply: 10 to 30VDC, 4W max.
- Protection class: IP65
- I/O: 2 inputs, 2 outputs; optocoupled

DS2400N

- Scan rate: up to 1000scans/s
- Reading range: 70 to 600mm
- Max. resolution: 0.12mm (5mils)
- Power supply: 10 to 30VDC, 4W max.
- Protection class: IP65
- I/O: 2 inputs, 2 outputs; optocoupled
- Operating temperature:
 - -35°C to 45°C (subzero model)
 - 0°C to 45°C (standard model)

DS4800

Automated warehousing

- Medium/small conveyor sorting
- Pallet reading
- Automated storage and retrieval systems
- Picking systems
- Receiving / shipping systems
- Low temperature warehouses

Automated Shopfloor

- Item and part tracking
- Process control systems
- Overall production traceability
- Packaging and compliance

DS4800

- Manually adjustable focus with locking
- Ambient light immunity for outside applications
- Integrated multi-language display for setup, monitoring, and diagnostics
- Subzero model (-35°C) with window defrost
- ACR4™ Advanced Code Reconstruction
- Integrated oscillating mirror model available
- ID-NET™ embedded interface for high speed communication network
- All 1D codes including GS1

DS4800

- Scan rate: up to 1000scans/s
- Reading distance: up to 1000mm on 0.50mm (20mils) codes
- Depth of field: up to 600mm on 0.50mm (20 mils) codes
- Max. resolution: up to 0.20mm (8mils)
- Connectivity: RS232, RS485
- I/O: 2 inputs, 2 outputs; optocoupled
- Power supply: 10 to 30VDC; 6W max.
- Protection class: IP65
- Operating temperature: -35°C to 50°C (subzero model)
- 0°C to 50°C (standard model)

AL5010

Automated warehousing

- Picking systems
- Pallet reading
- Label print and apply verification
- Receiving / shipping systems
- Automated storage and retrieval systems
- Process control systems

AL5010

- Largest depth of field of any mid-range laser barcode reader on the market
- PackTrack™ advanced tracking allows closer package spacing while maintaining package ID
- Integrated web server with monitoring support for iPhone and iPads
- Multi-language integrated GUI
- Easy 'plug and play' replacement
- Flexible connectivity with on board EtherNet/IP, Ethernet TCP/IP

AL5010

- Scan rate: up to 1200scans/s
- Depth of field: up to 1125mm on 0.50mm (20 mils) codes
- Max. resolution: up to 0.20mm (10mils)
- Connectivity: RS232, RS485, EtherNet IP, Ethernet TCIP/IP
- I/O: 4 programmable relays, 3 to 60VDC; optocoupled (Enhanced Interface Module)
- Power supply: 12 to 30VDC; 25W max.
- Protection class: IP65
- Operating temperature: 0°C to 50°C



AL5010



2K Series:
DS2100N
DS2400N



DS4800

DIMENSIONER

APPLICATIONS

DM3610

- Parcel revenue recovery
- Distribution Center spatial management
- Trailer load planning
- Automated shipping and manifesting systems



DM3610

HIGHLIGHTS

DM3610

- Certified for Legal for Trade applications
- Works for cuboidal, near-cuboidal, and irregular package flows
- Works for singulated and non-singulated package flows
- Use in multiple head configurations to reduce shadowing

TECHNICAL DATA

DM3610

- Accuracy of $\pm 5\text{mm}$ at transport speeds up to 3.1 m/s
- Maximum box size 2450mm x 1200mm x 900mm for a single head
- Operating temperature: 0°C to 50°C
- IP 65

CONNECTIVITY DEVICES

Wide range of connectivity for the identification product range with standard IP65 (NEMA4) protection class and operating temperature up to 50°C.

CBX SERIES

- Simplified wiring to speed up installation
- Scalable and modular connectivity
- Base and extended models
- Modular field bus connectivity
- Optional backup/restore module
- Optional display
- Low temperature model

QL SERIES

- Easy, fast, modular and cost-effective solution with 'plug-in connection'
- Ethernet TCP/IP and EtherNet IP (QL500)

SC SERIES

- Protection class: IP65 (NEMA4)
- Operation temperature: 0 to 50°C
- Network or cluster controller
- Dedicated data-collector for maximum reading performance
- Scalable and modular connectivity
- Backup/restore module
- Maximum compatibility and scalability
- Ethernet TCP/IP, EtherNet IP, Profibus, DeviceNet (QLM series)

AL 5010 INTERFACE MODULES

- Simplified wiring for fast installation
- Connectivity for Ethernet TCP/IP, Ethernet IP
- Profibus, DeviceNet and other common networks (Enhanced)
- Supports high voltage relays offering mini-controller capability (Enhanced)
- Dimensions: 93 x 136 x 65mm (Basic), 134 x 191 x 67mm (Enhanced)
- Supply Voltage 12-30 VDC, 25 W Max



SC SERIES

CBX SERIES



QL SERIES



AL5010 INTERFACES MODULE

HEADQUARTERS

Datalogic Automation Srl

Via Lavino, 265
40050 Monte San Pietro - Bologna - Italy
Tel: +39 051/6765611
info.automation.it@datalogic.com

BRANCHES AND SALES OFFICES

EUROPE BENELUX

Datalogic Automation Benelux

Newtonweg 3
4104 BK Culemborg - The Netherlands
Tel. +31 345/589489
info.automation.nl@datalogic.com

FRANCE

Datalogic Automation Srl

Succursale en France
Le Parc Technologique de Lyon
333 cours du 3ème Millénaire - Le Pôle
69800 Saint Priest
Tél. +33 (0)4/72476180
info.automation.fr@datalogic.com

GERMANY

Datalogic Automation Srl

Niederlassung Central Europe
Gottlieb-Stoll-Straße 1,
73271 Holzmaden
Tel. +49 7023 7453-100
info.automation.de@datalogic.com

ITALY

Datalogic Automation Italy

Via Lavino, 265
40050 Monte San Pietro - Bologna
Tel. +39 051/6765611
info.automation.it@datalogic.com

Via Taormina 1
20093 - Cologno Monzese (MI) Italy
Tel. +39 02 25151211
info.automation.it@datalogic.com

Via Le Gorrey, 10 11020, Donnas - Aosta
Tel. +39-0125-8128201
info.automation.it@datalogic.com

SPAIN

Datalogic Automation Iberia

Sucursal en España
C/ Frederic Mompou 4 esc A, 4º puerta 3ª
08960 Sant Just Desvern - Barcelona
Tel. +34 (0)93/4772059

NORDIC

Datalogic Automation AB

Höjdrodergatan 21
21239 Malmö - Sweden
Tel. +46 (0)40/385000
info.automation.se@datalogic.com

UNITED KINGDOM

Datalogic Automation UK

Datalogic House
Dunstable Road, Redbourn - Herfordshire
AL3 7PR
Tel. +44 (0) 1582 791750
info.automation.uk@datalogic.com

TURKEY

Datalogic ADC Turkey

Merkezi Italya Istanbul Merkez Şubesi Süleyman
Seba Cad. No:48 BJK Plaza A. Blok Kat:4 D.44
34357 - Istanbul - Turkey
Tel. +90 212 396 1550
info.adc.tr@datalogic.com

NORTH AMERICA

Datalogic Automation Inc

511 School House Road
Telford, PA 18969-1196 - United States
Tel. +1-800-BAR-CODE or +1-215-723-0981
info.automation.us@datalogic.com

Datalogic Automation Inc

MACHINE VISION
5775 W Old Shakopee Rd
STE 160, Bloomington, MN 55437
United States
Tel. +1-952-996-9500
info.automation.us@datalogic.com

SOUTH AMERICA

Datalogic Brazil

Avenida Olivio Roncoletta, 465
Bairro Vila Hortolandia Jundiã (SP), Brazil
Tel. +55 11 29232600
info.automation.br@datalogic.com

APAC

Australia-New Zealand

Datalogic Automation Pty Ltd

Unit 130, 45 Gilby Road
Mt Waverley - Victoria, 3149 - Australia
Tel. +61 (0)3/95589299
info.automation.au@datalogic.com

CHINA

Datalogic Automation Asia

2nd Floor, 10 Building, Dayuan Industrial Zone,
No.1, Pingshan 1st Road,
Liuxuan Blvd. Xili, Nanshan District,
518054, Shenzhen, China
Tel: +86 (0)755-8629 6779
info.automation.cn@datalogic.com

Suite 1301, Hua Rong Plaza,
1289 South Pudong Road, Pudong District
Shanghai 200120
Tel: +86 (0)21-5836 6692
info.automation.cn@datalogic.com

Floor 20, Room 2019, Building 2,
16 West Nan San Huan Road
Fengtai District, Beijing
Tel: +86 (0)10-8757 6375
info.automation.cn@datalogic.com

1202, Excellence Build, 128 Yanji Road,
Shibei District, Qingdao, China
Tel: +86 (0)532 55787889

JAPAN

Idec Auto-Id Solutions Corporation

8-10, Shioe 5-chome, Amagasaki Hyogo,
Japan 661-0976
Tel. +81-6-7711-8880
www.idec.com

Rev. 13_02/2016



9C0002870

Product and Company names and logos referenced may be either trademarks or registered trademarks of their respective companies. We reserve the right to make modifications and improvements.



DATALOGIC
THE VISION IS YOURS

www.datalogic.com